

## 2.4 CABLE PROTECTION Corrugated pipe PE

Application: Protection ELECTRICAL and TELECOMMUNICATION CABLES  
 Standard: UNE-EN 61386 -1 - 24  
 Joint system: Coupling sleeves  
 Marking: Accordind to specification  
 Color: Red, Green, other color to consult  
 Availability: - In rolls of 100 m DN 40 to 63  
 - In rolls of 50 m DN 90 to 125  
 - In rolls of 25 m DN 160 to 200  
 - In bars of 6 m from diameter 63 to diameter 315mm



### ROLLS and/or BARS.

DN/OD mm	DI/ID mm	Price €/m	Price sleeve €/u
40	---	---	---
50	40.0	1,10	0,45
63	51.0	1,23	0,46
90	74.4	1,79	0,87
110	92.5	2,15	1,43
125	105.5	3,23	2,09
160	136.6	3,88	2,81
200	169.7	5,78	4,60
250*	218,8	12,60	7,43
315*	273,0	17,89	-

Table keys: DN /OD= outside diameter (External diameter). DI/ID = Internal diameter

- The price PVP of the tube includes the price of the sleeve. The cable guide wire included only for the rolls.

\* DN 250 and 315 only in bars.

\* DN315 Joint system integrated in PP , in HDPE unión with sleeve.